



Calhoun: The NPS Institutional Archive

Theses and Dissertations

Thesis Collection

1980-06

Submarine hydraulic control analysis

Bower, Michael J.

Monterey, California. Naval Postgraduate School

<http://hdl.handle.net/10945/19078>



Calhoun is a project of the Dudley Knox Library at NPS, furthering the precepts and goals of open government and government transparency. All information contained herein has been approved for release by the NPS Public Affairs Officer.

Dudley Knox Library / Naval Postgraduate School
411 Dyer Road / 1 University Circle
Monterey, California USA 93943


<http://www.nps.edu/library>

DUDLEY KNOX LIBRARY
NAVAL POSTGRADUATE SCHOOL
MONTEREY CALIF 93940



NAVAL POSTGRADUATE SCHOOL

Monterey, California



THESIS

SUBMARINE HYDRAULIC CONTROL ANALYSIS

by

Michael J. Bower

June 1980

Thesis Advisor:

T. M. Houlihan

Approved for public release; distribution unlimited

T195711

REPORT DOCUMENTATION PAGE

READ INSTRUCTIONS
BEFORE COMPLETING FORM

1. REPORT NUMBER		2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Subtitle) SUBMARINE HYDRAULIC CONTROL ANALYSIS			5. TYPE OF REPORT & PERIOD COVERED Master's Thesis; June 1980
			6. PERFORMING ORG. REPORT NUMBER
7. AUTHOR(s) Michael J. Bower			8. CONTRACT OR GRANT NUMBER(s)
9. PERFORMING ORGANIZATION NAME AND ADDRESS Naval Postgraduate School Monterey, CA 93940			10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
11. CONTROLLING OFFICE NAME AND ADDRESS Naval Postgraduate School Monterey, CA 93940			12. REPORT DATE June 1980
			13. NUMBER OF PAGES 65
14. MONITORING AGENCY NAME & ADDRESS (if different from Controlling Office)			15. SECURITY CLASS. (of this report) Unclassified
			15a. DECLASSIFICATION/DOWNGRADING SCHEDULE
16. DISTRIBUTION STATEMENT (of this Report) Approved for public release; distribution unlimited			
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different from Report)			
18. SUPPLEMENTARY NOTES			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number) Hydraulics, submarine hydraulics, controls, controls analysis			
20. ABSTRACT (Continue on reverse side if necessary and identify by block number) A mathematical model was developed to include the effects in the submarine hydraulic system dynamic performance analysis. The project was undertaken in an effort to demonstrate the necessity of coupling the entire hydraulic power network for an accurate analysis of any of the subsystems rather than the current practice of treating a component loop as an isolated system. It was intended that the line model could be coupled			

with individual elements in modular computer programs to facilitate design and alteration decisions.

The line model was developed and coupled with a submarine driving-system servo-loop in order to demonstrate the above premises. However, due to programming difficulties additional work is necessary to successfully complete the analysis.

Approved for public release; distribution unlimited

Submarine Hydraulic Control Analysis

by

Michael J. Bower
Lieutenant, United States Navy
B.S., University of Kansas, 1972

Submitted in partial fulfillment of the
requirements for the degree of

MASTER OF SCIENCE IN MECHANICAL ENGINEERING

from the

NAVAL POSTGRADUATE SCHOOL
June 1980

ABSTRACT

A mathematical model was developed to include line effects in the submarine hydraulic system dynamic performance analysis. The project was undertaken in an effort to demonstrate the necessity of coupling the entire hydraulic power network for an accurate analysis of any of the subsystems rather than the current practice of treating a component loop as an isolated system. It was intended that the line model could be coupled with individual elements in modular computer programs to facilitate design and alteration decisions.

The line model was developed and coupled with a submarine driving-system servo-loop in order to demonstrate the above premises. However, due to programming difficulties additional work is necessary to successfully complete the analysis.

TABLE OF CONTENTS

I.	INTRODUCTION -----	11
	A. GENERAL DISCUSSION -----	11
	B. THE NEED FOR A LINE MODEL -----	11
	C. POTENTIAL FOR SYSTEM MODEL -----	12
II.	SYSTEM MODELED -----	14
	A. MAGNITUDE -----	14
	B. REALISM -----	14
III.	HYDRAULIC FLUID -----	16
	A. TYPE -----	16
	B. PROPERTIES -----	16
	1. Density -----	16
	2. Cubical Expansion Coefficient -----	17
	3. Viscosity -----	17
	4. Bulk Modulus -----	20
	C. LIMITATIONS -----	20
IV.	MODEL DEVELOPMENT -----	21
	A. SYSTEM OPERATION -----	21
	B. SERVO-SYSTEM -----	23
	1. Servovalve -----	23
	a. Flow Paths -----	23
	(1) Null Position -----	26
	(2) Valve Spool Off-Centered Left ----	27
	(3) Valve Spool Off-Centered Right ---	28
	2. Lines -----	28
	a. Flow and Pressure -----	28
	(1) Node Five -----	30

(2) Node Seven -----	32
(3) Node Nine -----	33
b. Secondary Components Effects -----	34
(1) Branch Lines -----	34
(2) Minor Components -----	34
(3) Major Components -----	35
(4) Combined Effects -----	36
3. Cylinder and Piston -----	36
a. Fluid Dynamics -----	36
(1) Flow -----	36
(2) Pressure -----	39
b. Piston Dynamics -----	40
C. PROGRAM -----	41
V. SUMMARY -----	42
A. CONCLUSIONS -----	42
B. RECOMMENDATIONS -----	42
APPENDIX A DETERMINATION OF SERVOVALVE VOLUME -----	43
APPENDIX B NULL FLOW PRESSURE COEFFICIENT DETERMINATION	44
APPENDIX C EMPIRICAL VALVE LEAKAGE COEFFICIENT -----	44
APPENDIX D DETERMINATION OF MAXIMUM VALVE TRAVEL -----	46
APPENDIX E LOSS COEFFICIENT DUE TO ABRUPT AREA CHANGES -	48
APPENDIX F SEAL LEAKAGE COEFFICIENTS -----	49
APPENDIX G MINOR COMPONENT ANALYSIS -----	51
APPENDIX H EFFECTIVE LENGTH OF MAJOR VALVES -----	53
APPENDIX I PROGRAM -----	54
LIST OF REFERENCES -----	63
INITIAL DISTRIBUTION LIST -----	65

LIST OF TABLES

TABLE I.	LINE SEGMENT DATA	-----	37
TABLE II.	MAJOR COMPONENT DATA	-----	38

LIST OF DRAWINGS

1. Stern Planes System -----	15
2. Stern Planes Control Circuit -----	22
3. Servovalve - RAM Hydraulic Loop -----	24
4. Servovalve -----	25
5. Stern Planes Hydraulic System Schematic -----	29
6. Line Node Identification -----	30
C-1 Leakage Flow Versus Valve Position -----	44
D-1 Valve Test Flow Path -----	46
E-1 Flow At An Abrupt Area Change -----	48

ABBREVIATIONS

A	area (in^2)
BV	blocking valve
c or c_1	constant
C_d	orific flow discharge coefficient
C_{el}	coefficient of external leakage ($\text{in}^3/\text{sec}/\text{psi}$)
C_{il}	coefficient of cross-port leakage ($\text{in}^3/\text{sec}/\text{psi}$)
cs	centstokes
d	differential operator
D	diameter
d_l	land diameter of valve (in)
D_r	piston tail rod diameter (in)
DV	deceleration valve
e	exponential (2.71828...)
F_L	load force
$^{\circ}\text{F}$	degrees Fahrenheit - temperature (lb)
K	loss coefficient due to abrupt area change
K_{co}	null flow pressure coefficient ($\text{in}^3/\text{sec}/\text{psi}$)
L	length (in)
L_{cy}	total cylinder length (in)
L_e	effective length (in)
L_o	length available for ram to travel with ram in center position (in)
m_{oil}	mass of oil (slugs)
m_r	mass of ram (slugs)
M_T	total mass (slugs)
MIL-L	military lubricant specifications
P	pressure (psi)
$\dot{P} = dP/dt$	change in pressure with respect to time (psi/sec)
P_o	reference pressure (psi)
psi	pounds per square inch - pressure
ΔP	differential pressure (psi)

Q_{el}	external leakage flow (in^3/sec)
Q_{il}	internal cross port flow (in^3/sec)
Q_{in}	supply flow from header (in^3/sec)
Q_r	return flow to header (in^3/sec)
SAE	Society of Automotive Engineers
SG	specific gravity
SSU	Saybolt Seconds Universal
t	time (sec)
T	temperature ($^{\circ}\text{F}$)
T_o	reference temperature ($^{\circ}\text{F}$)
t_p	piston thickness (in)
$\dot{V} = dV/dt$	changes in volume with respect to time (in^3/sec)
V_o	reference volume (in^3)
w	flow area coefficient (in^2/in)
X_r	ram position (in)
\dot{X}_r	ram velocity (in/sec)
\ddot{X}_r	ram acceleration (in/sec^2)
X_v	servovalve spool position (in)
X_{vm}	maximum servovalve spool position (in)
α	cubical expansion coefficient ($^{\circ}\text{F}^{-1}$)
β	bulk modulus (psi)
β_l	liquid bulk modulus (psi)
λ	absolute viscosity temperature coefficient
ρ	density (slug/in^3)
ρ_o	reference density (slug/in^3)
ρ_{w60}	density of water at 60°F (slug/in^3)
μ	absolute viscosity ($\text{lb sec}/\text{in}^2$)
ν	kinematic viscosity (in^2/sec)
ω_h	hydraulic natural frequency

I. INTRODUCTION

A. GENERAL DISCUSSION

The vast majority of hydraulic systems currently in use are of a dedicated type. That is, they are designed for a specific function with consistent and well defined constraints. In most cases they are further limited to a loop in which the pump supplies power to a single power element. Such systems can be delivered as compact units with a minimum of connecting piping. Some examples of dedicated systems in Naval use are: surface ship steering units, gun mount train and elevation units, and ammunition conveyor systems.

Although submarines have employed dedicated systems in the past, all modern U.S. submarines use constant pressure systems [Ref. 1, Tab. 561-1]. The constant pressure systems contrast with the dedicated type in that the supply and return headers extend the entire length of the ship and serve a multitude of power elements. The total piping length of these systems may exceed the length of the ship by a factor of four or more.

B. THE NEED FOR A LINE MODEL

For the packaged configuration of the dedicated system, with its relatively short piping lengths, the current practice of neglecting line dynamics and lumping the system volume has produced acceptable analytical results. However, even in systems with low line-volume to total-volume ratios, the computed values of the hydraulic natural frequency (ω_h)

are frequently in excess of 40% higher than measured values [Ref. 2]. Since ω_h sets the upper limit on system response and is affected by the volume as well as line dynamics, a model which includes these factors would undoubtedly produce more accurate results.

It was the intent of this project to demonstrate that the submarine hydraulic system, with its extremely long lines, requires that the line dynamics be included to achieve any degree of accuracy in analytical solutions.

C. POTENTIAL FOR SYSTEM MODEL

Discussions between the author and Mare Island Naval Shipyard Hydraulic Design Division personnel (code 260), as well as a Naval Sea Systems Command representative [Refs. 2 and 3], disclosed that there is currently no computer program to model the dynamic behavior of a submarine hydraulic system. Such a program would be useful in the design of new systems, both for sizing of lines and elements and for determining the response of components served. For existing systems, it would allow a determination of the effects of alterations prior to their implementation.

Additionally, a computer program of a dynamic system model would be advantageous in analyzing vibrations transmitted through the system. The "noise" generated by vibrations is a critical element of the "Submarine Sound Quieting Program," while the fatigue due to vibrations is important to the life of mechanical elements in the system, especially the seals [Refs. 5,6, and 7].

The development of a dynamic line model which could be programmed in a modular format and coupled with models for the individual elements would facilitate the creation of such an overall system model.


II. SYSTEM MODELED

A. MAGNITUDE

It was recognized early in the undertaking that it would not be possible to develop a model for an entire submarine hydraulic system in the time available. For this reason, the stern diving planes servo-loop was chosen for the primary development (Fig. 1). This sub-system was considered to be representative of one of the more complex loops in the overall system. (a loop being defined as the fluid path through a control valve - to the power element - back through the control valve). Successful modeling of the stern planes servo-system would readily permit expansion of the system to include the fairwater planes and rudder loops in parallel operations. With these three sub-systems modeled, the remainder of the hydraulic system could be relatively easily developed.

B. REALISM

An operational ship's hydraulic system was deemed essential as the basis for the model, as it would allow the computed parameters to be compared with actual performance data. The hydraulic plant of USS PERMIT (SSN 594) was chosen as the system to be modeled. It was considered representative of a modern submarine hydraulic system and the technical information was readily available at Mare Island Naval Shipyard.



STERN PLANES SYSTEM

Figure 1

III. HYDRAULIC FLUID

A. TYPE

The hydraulic oil used in all U.S. submarine internal high pressure (3000 psi) systems is Navy symbol 2190TEP. This is a petroleum based fluid conforming to military specification MIL-L-17331 [Ref. 8]. It exhibits approximately the same characteristics as an SAE-30-Detergent motor oil.

B. PROPERTIES

1. Density

The density (ρ) of the oil was obtained from Ref. 9 in terms of specific gravity (SG). The values supplied were

$$SG = 0.896 \quad \text{at } 74^{\circ}\text{F.}$$

$$SG = 0.0901 \quad \text{at } 60^{\circ}\text{F.}$$

The density of water at 60 degrees Fahrenheit is 9.3475×10^{-5} (slug/in³) and is assumed to be the reference for specific gravity unless otherwise specified [Ref. 10]. Specific gravity is defined as the ration of the density of the oil at the given temperature to that of water at 60 degrees Fahrenheit.

$$SG = \rho_o / \rho_{w60} \tag{1}$$

Solving for the density of oil at temperature (T)

yields

$$\rho = 8.4221 \times 10^{-5} \text{ slug/in}^3 \text{ at } 60^{\circ}\text{F}$$

$$\rho = 8.3754 \times 10^{-5} \text{ slug/in}^3 \text{ at } 74^{\circ}\text{F}$$

2. Cubical Expansion Coefficient

The cubical expansion coefficient (α) is the fractional change in volume of the fluid due to a change in temperature and is used in the determination of density, viscosity (μ, ν), and bulk modulus (β) values.

Density values arrived at in the previous section were used to obtain a value for the cubical expansion coefficient.

Using the form given in Ref. 11,

$$\rho(P, T) = \rho_o [1 + (P - P_o)/\beta - \alpha(T - T_o)] \quad (2)$$

where the subscript ($_o$) denotes reference values of one atmosphere of pressure and 60°F temperature.

Since the values for the density of the oil were obtained at one atmosphere

$$P = P_o$$

equation (2) reduces to

$$\rho = \rho_o [1 + \alpha (T - T_o)] \quad (2a)$$

Inserting appropriate values into (2a) and solving for α yields

$$\alpha = 3.9638 \times 10^{-4} \text{ }^{\circ}\text{F}^{-1}$$

3. Viscosity

a. Kinematic Viscosity

Reference 12 specifies that 2190TEP oil shall have a kinematic viscosity (ν) of 190SSU (Saybolt Seconds Universal) at a temperature of 130°F .

Using the standard conversion [Ref. 14] for kinematic viscosity, where the time (t) is greater than 100 seconds (SSU)

$$\nu = 0.220 t - (135/t) \quad (3)$$

yields

$$\nu = 41.09 \text{ cs} \quad \text{at } 130^{\circ}\text{F}$$

$$\nu = 92.03 \text{ cs} \quad \text{at } 100^{\circ}\text{F}$$

Converting from centistokes (cs) to English units was accomplished with the conversion factor (Ref. 15) of 1.549×10^{-3} (in^2/sec)/cs. Thus the values obtained for kinematic viscosity were

$$\nu = 0.06367 \text{ in}^2/\text{sec} \text{ at } 130^{\circ}\text{F}$$

$$\nu = 0.1427 \text{ in}^2/\text{sec} \text{ at } 100^{\circ}\text{F}$$

b. Absolute Viscosity

Knowing values of density and kinematic viscosity permits the determination of absolute viscosity (μ).

$$\mu = \rho \nu \quad (4)$$

Using the form presented in Ref. 16,

$$\mu = \mu_0 e^{-\lambda (T - T_0)} \quad (5)$$

at one atmosphere of pressure, where λ is the temperature coefficient of absolute viscosity with units of ($^{\circ}\text{F}^{-1}$).

Combining equations (4) and (5) and then solving for lambda gives

$$\lambda = \ln (\rho_0 \nu_0 / \rho \nu) / (T - T_0) \quad (6)$$

Arbitrarily setting

$$T_0 = 100^{\circ}\text{F} \quad \text{and} \quad T = 130^{\circ}\text{F}$$

in conjunction with values of density and kinematic viscosity at these temperatures yields

$$T_o = 100$$

$$T = 130^{\circ}\text{F}$$

$$\rho_o = 8.2886 \times 10^{-5}$$

$$\rho = 8.1884 \times 10^{-5}$$

$$\nu_o = 1.427 \times 10^{-1}$$

$$\nu = 6.367 \times 10^{-2}$$

Substituting these values into equation(6) produced a value of

$$\lambda = 2.731 \times 10^{-2} \text{ }^{\circ}\text{F}^{-1}$$

Reference 17 presents the pressure conversion for absolute viscosity as

$$\log_{10}(\mu/\mu_o) = cP \quad (7)$$

However, as the other functions are related by the difference in pressure divided by the bulk modulus ($\Delta P/\beta$), it would seem reasonable to assume that c in equation (7) has a form of (c_1/β). This would then yield an equation for absolute viscosity at constant temperature of

$$\mu = \mu_o e^{-(c_1 \Delta P/\beta)} \quad (8)$$

Lacking any other information, c_1 was set equal to one, and a final form for absolute viscosity was formulated as

$$\mu = \mu_o e^{((P/\beta) - \lambda(T-T_o))} \quad (9)$$

where

$$P = P - P_o$$

P = reference pressure (o psig)

P = system pressure (psig)

β = system effective bulk modulus (psi)

T = system temperature ($^{\circ}\text{F}$)

T_o = reference temperature ($^{\circ}\text{F}$)

4. Bulk Modulus

Although the literature on hydraulic systems indicated that the bulk modulus (β) would be supplied with the oil, visual inspection of shipping containers and bills of lading proved futile. Likewise, the military specifications (MIL-L-17331) failed to produce any worthwhile information in this regard. A nominal value of bulk modulus for the oil was therefore assumed to be 220,000 psi, as recommended in Ref. 18.

C. LIMITATIONS

In a further effort to maintain the scope of the project within reasonable constraints, it was decided to treat the temperature as constant. Inferences drawn from the Naval Ships' Technical Manuals previously cited and the author's own experience, indicated that a temperature of 130°F was a reasonable choice. With this value of temperature, the equations for the other properties were simplified.

From equation (2)

$$\rho = 8.188 \times 10^{-5} + 8.4221 \times 10^{-5}(P/\beta) \quad (10)$$

and equation (9) yields

$$\mu = 5.213 \times 10^{-6} e^{(P/\beta)} \quad (11)$$


IV. MODEL DEVELOPMENT

A. SYSTEM OPERATION

Submarine steering and diving control surfaces (rudder and diving planes) are positioned through mechanical linkages by hydraulic rams. Each surface has normal as well as alternate sources of hydraulic and electrical power to ensure reliability. For the purpose of model development, only the normal mode of the stern planes was considered.

The normal mode of operation for the SSN 594 class of submarine, employs a position control electro-hydraulic servo-loop (Fig. 1). In this type of system (Fig.2), control station operator manually positions a stick to achieve a desired angle of inclination of the planes. This produces an electrical signal which is summed with the feedback signal from the position output to create an error signal. The error signal is amplified and transmitted to the torque of the servovalve. The torque motor displaces the wand spring of the servovalve-pilot, which causes an imbalance in pilot pressure, which in turn shifts the main spool allowing the servovalve to pass oil to position the ram. As the desired position is attained, the error is reduced and the pilot returns the spool to a neutral positions, blocking the flow of oil.

Figure 2 Stern Planes Control Circuit



B. SERVO-SYSTEM

The area of interest for the model development was the hydraulic fluid flow in the servo-loop as depicted in Figure 3. By inputting the valve spool motion and ram load force as explicitly defined functions, the influences of the external factors involved in the feedback loops (the servovalve torque-motor and pilot valve, and the ram loading) were minimized. This permitted the generation of flow and pressure equations around the loop with a minimum of complications due to the ancillary characteristics.

1. Servovalve

The two servovalves commonly in use in the Submarine Force are both manufactured by the Sargent Corporation and are designated Sanders Model SV 438-10P and SV 438-15P [Ref. 19]. Design and performance of both valves are similar. The SV 438-10P which is installed in the (SSN-594), was used for this simulation. Figure 4 is a representative drawing of the actual valve employed - a four-land four-port element. However, comparison with the valve depicted in Figure 3 - a three-land four-port model - will show that the flow is essentially the same in both valves. It was considered easier to follow the flow paths of the valve in Figure 3.

All technical data for the servovalve was obtained from Ref. 20.

a. Flow Paths

The pilot valve flow was disregarded, as it has its own supply and return lines.




Figure 3 Servovalve-RAM Hydraulic Loop




Figure 4 Servovalve

Designating the supply flow as Q_{in} , the return flow as Q_r , and the other flows by their respective nodal points (Fig.3), the flow equations were derived. Using the form given in Ref. 21,

$$\Sigma Q_{in} - \Sigma Q_{out} = dV_o/dt + (V_o/\beta)dP/dt \quad (12)$$

the results were:

$$Q_{in} = Q_1 + Q_2 \quad (13)$$

$$Q_r = Q_3 + Q_4 \quad (14)$$

$$Q_1 = Q_3 + Q_5 + V_1 \dot{P}_1/\beta_1 + \dot{V}_1 \quad (15)$$

$$Q_2 = Q_4 + Q_6 + V_2 \dot{P}_2/\beta_2 + \dot{V}_2. \quad (16)$$

Here the volume across the lands of the valve was approximated as zero. The superscript ($\dot{}$) represents differentiation with respect to time.

Since the valve is manufactured from high strength alloys,

$$\dot{V}_1 = \dot{V}_2 = 0$$

$$V_1 = V_2,$$

as shown in Appendix A.

In addition to summing the flows through the valve, the flow rate was also defined through the lands for three different valve positions.

(1) Null Positions. In the centered (null) position, a critical-center servovalve will have leakage past the lands.¹ This flow is described in terms of null

¹For a comprehensive coverage of all terms used in this paper, the reader is referred to Ref. 2.

flow pressure coefficient (K_{co}), as

$$Q = \frac{1}{2}K_{co}(\Delta P). \quad (17)$$

The four node flows for $X_v = 0$ were

$$Q_1 = \frac{1}{2}K_{co}(P_{in}-P) \quad (18)$$

$$Q_2 = \frac{1}{2}K_{co}(P_{in}-P_2) \quad (19)$$

$$Q_3 = \frac{1}{2}K_{co}(P_1-P_r) \quad (20)$$

$$Q_4 = \frac{1}{2}K_{co}(P_2-P_r) \quad (21)$$

with

$$P_3 = P_4 = P_r.$$

See appendix B for values K_{co} used for the model.

(2) Valve Spool Off-Centered Left. The valve travel (X_v) was arbitrarily defined as positive to the left (Fig.3). Employing the orifice flow equation [Ref. 22] for the fluid passage through nodes one and four, and an empirical relationship for nodes two and three, the flow equations were determined to be

$$Q_1 = C_d A \sqrt{2(P_{in}-P_1)/\rho_l} \quad (22)$$

$$Q_2 = \frac{1}{2}K_{co} e^{-\lambda(X_v/X_{vm})^2} (P_{in}-P_2) \quad (23)$$

$$Q_3 = \frac{1}{2}K_{co} e^{-\lambda(X_v/X_{vm})^2} (P_1-P_r) \quad (24)$$

$$Q_4 = C_d A \sqrt{2(P_2-P_r)/\rho_r} \quad (25)$$

where $C_d = 0.61$ for full periphery rectangular ports and

$$A = \pi d_1 X_v \quad (26)$$

with d_1 defined as the land diameter of the spool valve.

Since a value of leakage flow was not determinable from Ref. 20, the empirical relationships of Appendices C and D were developed using Ref. 23 as a guide.

(3) Valve Spool Off-Centered Right. The equations for the "negative" flow direction were similar to those developed in the previous section, with the obvious exception that Q_2 and Q_3 became the principal flows. In order to maintain their flows as positive values, X_v was squared and included in the radical.

The form for X_v less than zero was

$$Q_1 = \frac{1}{2}K_{co}e^{-\lambda(X_v/X_{vm})^2}(P_{in}-P_1) \quad (27)$$

$$Q_2 = C_d w \sqrt{2X_v^2(P_{in}-P_2)/\rho_2} \quad (28)$$

$$Q_3 = C_d w \sqrt{2X_v^2(P_1-P_r)/\rho_2} \quad (29)$$

$$Q_4 = \frac{1}{2}K_{co}e^{-\lambda(X_v/X_{vm})^2}(P_2-P_r) \quad (30)$$

with

$$W = \pi d_1 \quad (31)$$

and all other variables as defined in previous sections.

2. Lines

The line equations were generated with the intention of accounting for all factors influencing the pressure and flow in the system. The schematic diagram of the actual system employed in this development is shown in Figure 5. For development purposes, only the odd numbered nodes are shown here as the even numbered side equations were identical.

a. Flow And Pressure

Disregarding all but the main line piping, the flow path from the servovalve to the ram was as depicted in Figures 3 and 5 were identified by the same numbers. The dynamics of these segments were then defined at each point when viewed as in Fig. 6.




Figure 5 Stern Planes Hydraulic System Schematic




FIGURE 6 LINE NODE IDENTIFICATION

Point A corresponds to nodal point (5) of Figure 3 and is considered to be located at the entrance of the pipe at its junction with the servovalve. Similarly, point B is located at the connection of the two different diameter pipes, in the entrance of the downstream pipe. It is equivalent to node (7) of Figure 3. Location C is just beyond the end of the line segment at the entrance to the cylinder, identified as node (9) in Figure 3.

Utilizing these definitions for the nodal points and viewing the direction of flow as always being from A to C, the dynamic equations for each element were developed.

(1) Node Five. The pressure and flow equations for node five were derived from Ref. 24.

$$Q_5 = Q_7 + V_{57} \dot{P}/B_{57} + \dot{V}_{57} \quad (32)$$

$$P_5 = P_1 - \rho_5 K_5 Q_5^2 / 2A_5^2 \quad (33)$$

The double-subscripted variables were employed to denote average values through the line segment, while the single-subscripted variables represent values at the particular node. Thus

$$V_{57} = A_5 L_{57} \quad (34)$$

with L_{57} being the actual length of pipe from node (5) to node (7) and

$$A_5 = \pi D_5^2 / 4. \quad (35)$$

As can be seen in Figure (6), the diameter of segment A-B (5-7) is constant and equal to the diameter at (5). The total volume and actual length will be developed further in later sections of this report.

The average pressure in the interval was

$$P_{57} = (P_5 + P_7) / 2 \quad (36)$$

with

$$P_{57} = \int \dot{P}_{57} dt. \quad (37)$$

The change in volume with respect to time (\dot{V}) was set equal to zero for all line segments, because the lines are made from high strength materials which do not permit any significant expansion or contraction. The exception to this would be in cases where there are flexible sections installed (Aeroquip -type hoses). There are numerous locations in the system where these are installed, but not in the servo-loop modeled. In the instances where flexible sections are incorporated in the system, an expression for the change in volume would have to be developed based on the properties of the material used.

The value of K_5 was based on an abrupt change in the cross-sectional area of a pipe, and the development is shown in Appendix E. As used in the above equations, the sign of K_5 changes with the direction of flow such that the second term of equation (33) will always reflect a pressure

loss for the referenced point. Thus, when flow is positive, as shown in Figure (6), P_1 will be greater than P_5 , but when the flow is reversed (negative in Figure (6)) P_5 will be greater than P_1 .

Q_7 is the flow at node (7) and will be defined in a subsequent section. P_1 is the pressure in the main servovalve cavity and is

$$P_1 = \int \dot{P}_1 dt \quad (38)$$

where \dot{P}_1 was introduced in section IV.B.1.a.

(2) Node Seven. The flow through node seven is exactly the same as that through node five, with subscripts changed to reflect the appropriate line segment.

$$Q_7 = Q_9 + V_{79} \dot{P}_{79}/B_{79} + \dot{V}_{79} \quad (39)$$

$$P_{79} = \int P_{79} dt.$$

The pressure at point (7), on the other hand, must reflect the losses due to flow in line segment (57).

This was accomplished with a combination of the equations in Ref. 24 with those in Appendix E:

$$P_7 = P_5 - 32\mu_{57}L_{e57}Q_{57}/A_5D_5^2 - 1.14\rho_{57}Q_{57}^2/A_5^2 - \rho_7K_7Q_7^2/2A_5^2. \quad (40)$$

The second term on the right side of equation (40) is the Hagen-Poiseuille term for fully developed laminar flow in pipes. The third term accounts for developing laminar flow. The final term accounts for the entry/exit loss at cross-sectional area changes, as shown in Appendix E.

All three terms must reflect a loss of pressure for flow in either direction. Since Q_{57} assumes a negative value for flow reversal, it presents no problem.

However, Q_{57}^2 will always be a positive quantity unless it is defined as

$$Q_{57}^2 = Q_{57} \cdot |Q_{57}|, \quad (41)$$

in which case the sign of Q_{57}^2 will reflect the direction of flow. As noted previously, K_7 determines the sign of the final term.

A_5^2 is used in the last term of equation (40), because the area employed is always that of the smaller of the two at a junction.

Previously undefined variables are

$$Q_{57} = (Q_5 + Q_7)/2 \quad (42)$$

$$Le_{57} = \text{effective length from (5) to (7)}.$$

Effective line length will be discussed in a later section.

(3) Node Nine. The pressure at point nine has the same form as that at seven

$$P_9 = P_7 - 32\mu_{79}Le_{79}Q_{79}/A_7D_7^2 - 1.14\rho_{79}Q_{79}^2/A_7^2 - \rho_9K_9Q_9^2/2A_7^2 \quad (43)$$

with

$$Q_{79}^2 = Q_{79} \cdot |Q_{79}| \quad (44)$$

for the reasons discussed in the previous section.

Flow through this junction is

$$Q_9 = Q_{11} + Q_{e1}. \quad (45)$$

Q_{11} will be defined with respect to ram flow in a following segment of the paper.

$$Q_{e1} = C_{e1}P_9. \quad (46)$$

The coefficient of external leakage (C_{e1}) is the allowable leak rate past the cylinder tail rods to the atmosphere.

Appendix F derives the values used, based on information contained in Ref. 25.

There were no volume terms included in equation (45) because the transition from the end of the line to the cylinder entrance was considered an infinitesimal distance.

b. Secondary Component Effects

It is readily apparent from a comparison of Figure (5) with Figure (3) that the simplified system omits numerous valves, fittings, and other miscellaneous elements which are installed between the servovalve and ram. Although these "secondary" components have a minor influence individually, when combined they contribute significantly to both static and dynamic characteristics of the system.

The approach taken in this development was to consider them in three categories: branch lines, minor components, and major elements.

(1) Branch Lines. Branch lines are the segments of pipe connected to the main line. They are subjected to system pressure but do not ordinarily allow fluid to flow. Gage lines, hand positioning branches, and capped sections were included in Figure (5).

These lines contribute only to the total system volume.

(2) Minor Components. The minor components were considered to be any elements installed in the system which contributed to the effective length and volume of the system but were not specifically listed in the list of major components [Ref. 26].

The elements in this group were ball valves, tees, and elbows. Reference 27 was used as the source for information on them and Appendix G explains their development for use in the overall analysis of the system.

(3) Major Components. The deceleration valves (decel) and the blocking valve were included as major components. These were listed in Ref. 26 with specific pressure and flow characteristics. The volumes employed were a "best estimate" based on diameter and the author's personal experience. The effective lengths were as determined from the procedure in Appendix H.

The function of the blocking valve is to transfer to an alternate source of hydraulic supply (the Vital System), in the event of a loss of main header pressure. As pressures in the two systems are ordinarily the same (within 100psi. of each other) and the valve has internal seals, cross-port leakage is negligible.

The deceleration valve is a cam operated full-flow valve which is installed to prevent over-travel of the ram. As the ram approaches its maximum limit of travel, a collar on the tail rod mechanically trips the decel can, shutting the deceleration valve. This permits a fluid cushion to arrest the ram travel rather than allowing it to a "hard-stop" (metal - to - metal) at maximum velocity. Motion in the reverse direction is permitted by flow through the internal check valve until the linkage allows the main deceleration valve to reopen.

(4) Combined Effects. The various elements were combined in tabular form for inclusion in the system analysis (Tables 1 and 2). These were input directly into the computer program to solve for the various parameters as discussed above.

3. Cylinder and Piston

The final element in the system is the cylinder and piston combination. Here the power is transmitted from the fluid to the stern planes by the piston and its associated linkages.

a. Fluid Dynamics

The pressure and flow equations assumed a form similar to those of the lines.

(1) Flow. The flow in the cylinder was described by

$$Q_{11} = Q_{i\ell} + \dot{V}_{11} + V_{11}\dot{P}_{11}/\beta_{11} \quad (47)$$

where

$$Q_{i\ell} = C_{i\ell}(P_{11} - P_{12}) \quad (48)$$

with

$$P_{11} = \int \dot{P}_{11} dt \quad (49)$$

$Q_{i\ell}$ is the internal leakage from the high pressure side to the low pressure side of the piston. The determination of $C_{i\ell}$ is shown in Appendix F. Flow was defined as positive from node (11) to node (12); thus, when P_{12} is greater than P_{11} , Q_i will assume a negative value as required by the line equations.

TABLE I LINE SEGMENT DATA

IDENTIFICATION	OD	TH	L	NTT	NTB	NL45	NL90	NVB	I
PROGRAM BLUEPRINT	in.	in.	in.						
7 (7-9) 1591	2.0	0.27	108	1	2	0	6	1	
1589	2.0	0.27	120	0	0	0	0	0	
7-1 1626	0.75	0.109	8	0	1	0	0	0	
7-2 1608	0.375	0.058	120	0	0	0	1	1	
7-3 1626	1.5	0.203	12	0	0	0	0	0	
8 (8-10) 1590	2.0	0.27	96	0	3	0	5	1	
1588	2.0	0.27	120	0	0	0	0	0	I
8-1 1620	0.75	0.109	8	0	1	0	0	0	
8-2 1609	0.375	0.058	120	0	0	0	2	1	
8-3 1621	1.5	0.203	12	0	0	0	0	0	
5 (5-7) 4500	1.90	0.25	48	0	0	0	1	0	I
6 (6-8) 4501	1.90	0.25	48	0	0	0	1	0	

OD - outside diameter

TH - wall thickness

L - length

NTT - number of flow through tees

NTB - number of branch flow tees

NL45- number of 45° elbows

NL90- number of 90° elbows

NVB - number of ball valves

IDENTIFICATION		ID	V	Q _{REF}	P _{LOSS}	T _{REF}	REF
PROGRAM	BLUEPRINT	in.	in. ³	GPM	psi	°F	slug/in ³
BV7	HSD79-9	1.46	20	50	50	120	8.68 x10 ⁻⁵
BV8							
DV7	HSD127-15	1.094	60	50	60	120	8.68 x10 ⁻⁵
DV8	HSD101-15						

TABLE II MAJOR COMPONENT DATA

$$\dot{V}_{11} = A_{11}\dot{X}_r \quad (50)$$

A_{11} is the effective piston area

$$A_{11} = \pi(D_{11}^2 - D_r^2)/4 \quad (51)$$

where D_{11} is the land diameter of the cylinder and D_r is the diameter of the piston tail-rod.

\dot{X}_r is the velocity of the ram.

$$V_{11} = A_{11}L_{11} \quad (52)$$

where

$$L_{11} = L_o + X_r \quad (53)$$

and $L_o = \frac{1}{2}(L_{cy} - t_p) \quad (54)$

L_{cy} is the length of the cylinder t_p

is the thickness of the piston. Ram position was defined as positive to the left in Figure (5), so that motion to the left increases V_{11} while movement of the piston to the right decreases V_{11} . For this reason, it was necessary to define

$$V_{12} = L_o - X_r \quad (55)$$

and ultimately

$$Q_{12} = -Q_{i1} - \dot{V}_{12} - V_{12}\dot{P}_{12}/\beta_{12}. \quad (56)$$

Thus, the various flows in the system would automatically assume the proper sign to reflect the direction of flow.

(2) Pressure. The pressure equation for the cylinder and piston arrangement became

$$P_{11} = P_9 - 32\mu_{11}L_{11}Q_{11}/A_{11}D_{11}^2 - 1.14 \rho_{11}Q_{11}^2/A_{11}^2. \quad (57)$$

There was no entry loss term because it was taken into account with P_9 . The other difference, with regard to the previous line loss equations, is that D_{11} is the

land diameter of the cylinder while A_{11} is the effective area of the piston. The effective area was used because Q/A is a velocity term employed in defining viscous loss. On the other hand, D_{11} was used to account for the surface area upon which the fluid is "dragging"; i.e., the walls of the cylinder. Since the tail rod is traveling at essentially the same velocity as the fluid, it contributes no losses due to viscosity.

As in previous sections, it was necessary to define

$$Q_{11}^2 = Q_{11} \cdot |Q_{11}| \quad (58)$$

to account for flow direction.

b. Piston Dynamics

Ram motion was defined in terms of position (X_r), velocity (\dot{X}_r), and acceleration (\ddot{X}_r).

$$X_r = \int \dot{X}_r dt \quad (59)$$

$$\dot{X}_r = \int \ddot{X}_r dt \quad (60)$$

$$\ddot{X}_r = (A_{11}P_{11} - A_{12}P_{12} - \dot{m}_{oil}\dot{X}_r - F_L) / M_T \quad (61)$$

The load force (F_L), as described at the outset, was input as a ramp function dependent on ram position and velocity.

The flow of oil (\dot{m}_{oil}) term was included to account for the force required to maintain the momentum of the oil. It was determined to be

$$\dot{m}_{oil} = \rho_{12}\dot{V}_{12} \quad \text{for } \dot{X}_r > 0 \quad (62)$$

and

$$\dot{m}_{oil} = \rho_{11}\dot{V}_{11} \quad \text{for } \dot{X}_r < 0. \quad (63)$$

The total mass of the system (M_T) was defined as the mass of the ram plus the mass of the oil from the low pressure side of the piston to the return tank, such that

$$M_T = m_r + \sum_{\text{ram}}^{\text{tank}} \rho_i V_i \quad (64)$$

where the subscript (i) indicates each main line segment (flow path) from the ram face to the return tank.

C. PROGRAM

The foregoing equations were re-arranged to yield the form shown in the attached computer program. They were modeled in a Continuous System Modeling Program (CSMP III) in the belief that it was the best modeling method available. However, numerous attempts failed to accomplish the desired result.

The algebraic equations form a loop for which no solution was found.

V. SUMMARY

A. CONCLUSIONS

It is felt that the development of the line equations demonstrates the necessity of including these factors in any in-depth analysis of the submarine hydraulic system. It is also the author's belief that the approach taken in this presentation will yield worthwhile results for any system employing extensive quantities of piping.

As stated in the introduction, a generalized computer program of this type would have many beneficial aspects for both the submarine designer as well as the operator.

B. RECOMMENDATIONS

The first recommendation is a possible means of clearing the algebraic loop problem currently preventing the program from executing. This would require clearing all of the pressure and flow equations of reference to any variables except for themselves or ones which directly invoke an integral. That is

$$P_7 = f(P_{79}, P_{57}, P_1, P_7, \text{etc.}) .$$

However, it could not take the form where P_7 was set equal to P_9 or any of the flow terms (Q_i), as they do not invoke an integral function.

The other possibility would be to locate another program which could efficiently handle both integral as well as simultaneous algebraic equations.

APPENDIX A

Determination of Servovalve Volume

No values were obtainable for the volume of the servovalve. Therefore, the following method was employed to obtain a realistic approximation.

Using nominal dimensions given in the technical manual [Ref. 20] and the knowledge that the valve is made of aluminum alloy, a volume to weight ratio was determined.

Dimensions 18.5 x 8.0625 x 9.5 in.

Specific Gravity of alloy approximately 2.8

Given weight 69 lb.

Density of water at 60°F. 62.4lb/ft³

$$V_{\text{body}} = 1417 \text{ in}^3$$

$$\gamma_{\text{alloy}} = 0.101 \text{ lb/in}^3$$

$$W = V\gamma = 143.3 \text{ lb} \quad \text{for a solid block}$$

then

$$w_{\text{given}}/W = 0.48 .$$

Thus the valve body weighs approximately half of what a solid block would weigh. It was therefore assumed that the volume of metal in the valve was 708in³. Further, estimating that the passages for the pilot system occupy half of the void area yielded a main valve volume of about 350 in³, and since this volume is that occupied by both the supply and the return segments of the valve, half was assigned to each.

$$V_1 = V_2 = 175 \text{ in}^3$$

APPENDIX B

Null Flow Pressure Coefficient Determination

The allowable null flow leakage was given as 600 cc/min. at 1200 psi. [Ref. 20]. This was converted to standard form of $(\text{in}^3/\text{sec})/\text{psi}$. as follows

$$K_{co} = 600(\text{cc.min})/1200 \text{ psi} \times 1 \text{ in}^3/16.39\text{cc} \times 1 \text{ min}/60 \text{ sec} .$$

This yielded

$$K_{co} = 5.0844 \times 10^{-4} (\text{in}^3/\text{sec})/\text{psi}.$$

and

$$\frac{1}{2}K_{co} = 2.5422 \times 10^{-4} (\text{in}^3/\text{sec})/\text{psi} .$$

APPENDIX C

Empirical Valve Leakage Coefficient

The leakage flow across a valve port decreases as the valve moves to block the port. Since a plot of leakage flow (Q_l) versus valve position (X_v) is symmetrical, with an exponential decay as shown in Fig. C-1, and exact data was not given for leakage other than the null position an empirical expression was developed.




Figure C-1 Leakage Flow vs Valve Position

The most appropriate expression to fit this curve took the form of

$$Q_{\ell}/Q_{\ell\max} = e^{-\lambda(X_v/X_{v\max})^2}$$

where

Q_{ℓ} = leakage flow at any valve position

$Q_{\ell\max}$ = maximum leak rate = $\frac{1}{2}K_{co}$

$X_{v\max}$ = maximum valve travel from null.

Representative values were then chosen such that

$$Q_{\ell}/Q_{\ell\max} = .02 \text{ at } X_v/X_{v\max} = .25$$

That is, at 25% of maximum valve travel leakage through the "blocked" port of the valve decreases to 2% of the null position leakage.

Solving for λ

$$\lambda = (\ln(Q_{\ell\max}/Q_{\ell})) / (X_v/X_{v\max})^2$$

$$\lambda = 62.6.$$

In reality λ could vary from near zero to about 100.

Realistically it would have a value between 50 and 100.

$\lambda = 65$ was chosen as the value to employ in this presentation.

The form used was

$$Q_{\ell} = \frac{1}{2}K_{co} e^{-\lambda(X_v/X_{v\max})^2}$$

with the determination of maximum valve travel (X_{vm}) shown in Appendix D.

APPENDIX D

Determination of Maximum Valve Travel

Reference shows that

$$Q_{\max} = 80 \text{ GPM} = 80 \times 231/60 \text{ in}^3/\text{sec}$$

at

$$T = 115^\circ\text{F}$$

$$\Delta P_{\text{total}} = 1200 \text{ psi}$$

$$\Delta P_{\text{port}} = 600 \text{ psi}$$

as depicted in Figure D-1.




Figure D-1 Valve Test Flow Path

Using the orifice equation

$$Q = C_d A (2\Delta P / \rho)^{\frac{1}{2}}$$

with

$$C_d = 0.61$$

$$\rho = 8.442 \times 10^{-5}$$

$$A = \pi d_1 X_v \text{ where } d_1 = 1 \text{ in.}$$

$$X_v = X_{vm}$$

$$Q = Q_m$$

such that

$$X_{vm} = (Q_m / \pi C_d d_1 (2\Delta P_p / \rho)^{1/2})$$

resulting in $X_{vm} = 0.0426$ in.

This value was used in spite of the fact that it seemed large for a "standard" pilot controlled servovalve.

APPENDIX E

Loss Coefficient Due To Abrupt Area Changes

The standard form of the pressure loss due to abrupt piping diameter change is given as

$$H_1 = KV^2/2g$$

where

H_1 is head loss, expressed in feet of fluid

V is fluid velocity

g is acceleration due to gravity.

Head loss can also be expressed as

$$H_1 = \Delta P/\alpha$$

$$\gamma = \rho g$$

and

γ is weight density

while velocity is

$$V = Q/A = 4Q/\pi D^2$$

combining the above equations

$$\Delta P = 8\rho KQ^2/\pi^2 D^4.$$

K is defined from Figure D-1

$$K = \frac{1}{2}(1-D_1/D_2) \quad \text{for } +Q$$

$$K = -(1-(D_1/D_2)^2)^2 \quad \text{for } -Q.$$

NOTE D_1 is always the smaller of the two diameters being considered.




Figure E-1 Flow at an Abrupt Area Change

APPENDIX F

Seal Leakage Coefficients

Seal leakage was based on permissible values listed in Naval Ship's Technical Manual, [Ref. 25.] The values used in this presentation were for "used" seals with maximum allowable leakage before replacement is required. This was felt to be reasonable since the operating temperature of the oil is normally greater than the test temperature, which will produce slightly higher leak rates.

The leak rates were given as one milliliter per ten cycles per inch of rod diameter for external leakage, and five milliliter per five minutes per inch of rod diameter for internal leakage. These were based on normal operating pressures and a fluid temperature of 100°F.

Operating pressures were assumed to be

$$P_{el} = 2000 \text{ psi}$$

$$P_{il} = 1000 \text{ psi}$$

where P_{el} is the pressure for external leakage and P_{il} is the pressure for internal leakage. A cycle was defined as the time to go from neutral (zero plane angle) to full rise to full dive and back to neutral position. For the system modeled, stern planes travel is plus or minus 27°. Thus, a full cycle would be four times this value, or 108°. The normal rate of travel is about five degrees per second. Thus, $108/5 = 21.6 \text{ sec/cycle}$ or approximately

3 cycles/min.

Since the tail rod used, had a diameter of four inches, the allowable external leakage was four milliliters per ten cycles.

Then

$$\frac{4\text{ml}}{10\text{cy}} \times \frac{1\text{cc}}{1\text{ml}} \times \frac{3\text{ cy}}{1\text{ min}} = 1.2\text{cc/min}$$

and

$$C_{el} = 1.2 \frac{\text{cc}}{\text{min}} \times \frac{1\text{ min}}{60\text{ sec}} \times \frac{1\text{ in}^3}{16.39\text{cc}} \times \frac{1}{2000\text{ psi}}$$

$$C_{el} = 6.1 \times 10^{-7} (\text{in}^3/\text{sec})/\text{psi}$$

Similarly the internal leakage for a land diameter of 8.25 inches, rounded to nine inches, was nine cubic centimeters per minute.

And

$$C_{il} = \frac{9}{60 \times 16.39 \times 1000}$$

$$C_{il} = 9.15 \times 10^{-6} (\text{in}^3/\text{sec})/\text{psi}$$

APPENDIX G

Minor Component Analysis

The values used in the derivation of the minor component effects, considered herein, were obtained from Crane Technical Paper No. 410, [Ref. 27].

The volume was determined to be

$$V = AL$$

where A was the cross-sectional area of the pipe entering or leaving the element and L was a value determined for each type of element. The values for L were chosen as

$$\text{Ball valves} \quad L = 3 \times D$$

$$\text{Tees} \quad L = 2 \times D$$

$$\text{Elbows} \quad L = 1.6 \times D$$

In cases where the element has differing entry and exit diameters, D is the larger of the two.

The values for the effective lengths were

$$\text{Ball valves} \quad L_e = 3 \times D$$

$$\text{Flow through tees} \quad L_e = 20 \times D$$

$$\text{Branch flow tees} \quad L_e = 60 \times D$$

$$45^\circ \text{ elbows} \quad L_e = 16 \times D$$

$$90^\circ \text{ elbows} \quad L_e = 30 \times D$$

where the diameters were as above. An additional factor of K (appendix E) would have to be included for diameter differences in the main flow path.

The value of effective length cited above, were determined for Reynolds numbers (R_e) greater than 1000. Therefore,

it was necessary to modify them

Since $R_e = 4Q/(\pi Dv)$

and $L_{ed} = L_{ec} R_e / 1000$ for $R_e < 1000$

with L_{ed} = the desired effective length

L_{ec} = the calculated effective length from above

then $L_e = L_{ec} (4Q/(\pi Dv)) \times 10^{-3}$

If $R_e \geq 1000$ then $L_e = L_{ec}$

so that for $4Q/\pi Dv > 1000$

or $Q\rho/D\mu \geq 785.4$ $L_e = L_{ec}$

and for $Q\rho/D\mu < 785.4$ $L_e = 1.273 \times 10^{-3} L_{ec} Q\rho/D\mu$

APPENDIX H

Effective Length of Major Valves

The standard head loss equation

$H_1 = K_V^2/2g$ was rearranged in the form

$$\Delta P/\rho g = KQ^2/2gA^2$$

This yielded

$$K = 2\Delta PA^2/\rho Q^2$$

since

$$A = \pi D^2/4$$

$$K = \pi^2 \Delta P D^4 / 8 \rho Q^2$$

and since

$$K = L_e/D$$

$$L_e = \pi^2 \Delta P D^5 / 8 \rho Q^2$$

To allow Q to be entered in the form presented (GPM),
a conversion was included.

$$231 \text{ in}^3/\text{gal} \times 1 \text{ min}/60 \text{ sec}$$

so that

$$Q \text{ (GPM)} \times 231/60 = Q \text{ (in}^3/\text{sec)}$$

and $L_e = .0832 \text{ PD}^5/\rho Q^2$

where

D = diameter of valve (in)

P = given pressure loss (psi)

Q = given flow (GPM)

ρ = density of fluid at given temperature (slug/in³)

TO EMPLOY:

SUPPLY LINES; D1 IS ALWAYS THE POINT CLOSEST TO THE
PUMP - THE UPSTREAM POINT

RETURN LINES; D1 IS ALWAYS THE POINT FARTHEST FROM
THE TANK - THE UPSTREAM POINT

DUAL DIRECTION (REVERSING) LINES; D1 IS THE POINT
NEAREST THE CONTROL ELEMENT (VALVE), VIEWED AS IF
THE LINE ALWAYS SUPPLIES PRESSURE TO THE POWER
ELEMENT

ENDMAC

INITIAL

CONSTANT KCCCC=600.,FT=1200.,LAMB=65.

VALVE LEAK RATE OF MAIN SPOOL

NOTE: LAMB IS STRICTLY EMPIRICAL AND BASED ON AN
AVERAGE CURVE OF LEAK-RATE VS VALVE DISPLACEMENT.

CONSTANT XVM=0.0425,DLV=1.0,CD=0.61,V1=175.,V2=175.

CONSTANT OD5=1.90,TH5=0.25,L5=48.0,NTB5=0.,NTT5=0.,...
NL45=0.,NL95=1.,NV5=0.

CONSTANT OD6=1.9,TH6=0.25,L6=48.0,NTB6=0.,NTT6=0.,...
NL46=0.,NL96=1.,NV6=0.

CONSTANT CD7=2.0,TH7=0.27,L7=228.0,NTB7=2.,NTT7=1.,NL47=0.,...
NL97=6.,NV7=1.

CONSTANT OD8=2.0,TH8=0.27,L8=216.0,NTB8=3.,NTT8=0.,NL48=0.,...
NL98=5.,NV8=1.

CONSTANT OD71=0.75,TH71=0.109,L71=8.0,NTB71=1.,NTT71=C.,...
NL471=0.,NL971=0.,NV71=0.

CONSTANT OD72=0.375,TH72=0.058,L72=120.0,NTB72=0.,NTT72=0.,...
NL472=0.,NL972=1.,NV72=1.

CONSTANT OD73=1.5,TH73=0.203,L73=12.0,NTB73=0.,NTT73=0.,...
NL473=0.,NL973=0.,NV73=0.

CONSTANT OD81=0.75,TH81=0.109,L81=8.0,NTB81=1.,NTT81=0.,...
NL481=0.,NL981=0.,NV81=0.

CONSTANT OD82=0.3750,TH82=0.058,L82=120.0,NTB82=0.,NTT82=0.,...
NL482.,NL982=2.,NV82=1.

CONSTANT OD83=1.5,TH83=0.203,L83=12.0,NTB83=0.,NTT83=0.,...
NL483=0.,NL983=0.,NV83=0.

CONSTANT PDR7=60.0,QDR7=50.0,RDR7=8.68E-05,VDV7=60.,DDV7=1.094

CONSTANT PER7=50.,QBR7=50.,RBR7=8.68E-05,VBV7=20.,DBV7=1.46

CONSTANT E=3.0E07,POIS=0.3

CONSTANT BO=200000.

CONSTANT PR=50.,PIN=3000.,FA=0.1,ODRE=2.0,THRE=0.148,VR=2750.

CONSTANT OILCC=9.0,CELCC=1.2,PCEL=2000.,PCIL=1000.

CONSTANT DLR=8.255,DRR=4.0,ODR=11.5,LCY=39.875,TR=5.125,MR=12.1

CONSTANT PI=3.141593

KCC=0.5*KCOCC/(PT*983.4)

THE VALUE OF (0.5) IS USED BECAUSE THE TECH. MANUAL
LISTS A LEAK-RATE FOR THE WHOLE VALVE; THE
VALUE SOUGHT IS THAT FOR HALF THE VALVE (ONE SET
OF PORTS).

KCOCC IS TECH. MANUAL LEAK-RATE IN (CC/MIN).

PT IS TEST PRESSURE USED TO ESTABLISH THE LEAK-RATE (PSI).

KCO IS LEAK-RATE IN ((IN**3/SEC)/PSI).

AG=CD*PI*DLV*SQRT(2.)

AG IS THE PRODUCT OF THE CONSTANT COEFFICIENTS USED IN
IN THE SERVO-VALVE EQUATION.

CFA=FA/1.4

FA IS THE FRACTION OF AIR ENTRAPPED IN THE SYSTEM,
EXPRESSED AS A PERCENTAGE OF THE TOTAL SYSTEM VOLUME.

CFA IS THE COEFFICIENT OF THE AIR TERM IN BULK MODULUS
CALCULATIONS.

K5P,K5M=ENTCO(D1,D5)
K6P,K6M=ENTCO(D2,D6)
K7P,K7M=ENTCO(D5,D7)
K8P,K8M=ENTCO(D6,D8)
K9P,K9M=ENTCO(D7,D11)
K10P,K10M=ENT CO(D8,D12)

THESE COEFFICIENTS ACCOUNT FOR EXIT LOSSES ONLY:
ENTRY LOSSES ARE CONSIDERED AS EXIT LOSSES FOR
THE NEXT ELEMENT UPSTREAM.

VP5,A5,LEP5,D5LA5,BCS5=VALE(PI,E,POIS,OD5,TH5L5,NTT5,NTB5,...
NL45,NL95,NV5)

VP6,A6,LEP6,D6LA6,BCS6=VALE(PI,E,POIS,OD6,TH6,L6,NTT6,NTB6,...
NL46,NL96,NV6)

VP7,A7,LEP7,D7,LA7,BCS7=VALE(PI,E,POIS,OD7,TH7,L7,NTT7,NTB7,...
NL47,NL97,NV7)

VP8,A8,LEP8,D8,LA8,B(S8=VALE(PI,E,POIS,OD8,TH8,L8,NTT8,NTB8,...
NL48,NL98,NV81)

V&B1,A7B1,LE7B1,D7B1,LA7B1,BCS71=VALE(PI,E,POIS,OD71,TH71,...
L71,NTT71,NTB71,NL471,NL971,NV71)

V7B2,A7B2,LE7B2,D7B2,LA7B2,BCS72=VALE(PI,E,POIS,OD72,TH72,...
L72,NTT72,NTB72,NL472,NL972,NV72)

V7B3,A7B3,LE7B3,D7B3,LA7B3,BCS73=VALE9PI,E,POIS,OD73,TH73,...
L73,NTT73,NTB73,NL473,NL973,NV73)

V8B1,A8B1,LE8B1,D8B1,LA8B1,BCS81=VALE(PI,E,POIS,OD81,TH81,...
L81,NTT81,NTB81,NL481,NL981,NV81)

V8B2,A8B2,LE8B2,D8B2,LA8B2,BCS82=VALE9PI,E,POIS,OD82,TH82,...
L82,NTT82,NTB82,NL482,NL982,NV82)

V8B3,A8B3,LE8B3,D8B3,LA8B3,BCS83=VALE(PI,POIS,OD83,TH83,...
L83,NTT83,NTB83,NL483,NL983,NV83)

BOI=1.0.BO
BCII=2.0*(1.0+POIS)/E
BI1=BOI+BC1I
BI2=BI1
BI5=BI1
BI6=BI1
BI7=BI1
BI8=BI1
BI9=BI1
BI10=BI1
BI11=BI1
BI12=BI1
BCDV8=BI1*VDV8
BCDV7=BI1*VDV7
BCBV8=BI1*VBV8
BCBV7=BI1*VBV7

BI57=BOI+BCS5/V57
BI68=BOI+BCS6/V68
BI79=BOI+(BCS7+BCS71+BCS72+BCS73+BCS74+BCDV7+BCBV7)/V79
BI81=BOI+(BCS8+BCS81+BCS82+BCS83+BCS84+BCDV8+BCBV8)/V*1

CQ57,CQ57S=LINCO(A5,D5,OD5)
CQ58,CQ68S=LINCO(A6,D6,OD6)
CQ79,CQ79S=LINCO(A7,D7,OD7)
CQ81,CQ81S=LINCO(A8,D8,OD8)
CQ11,CQ11S=LINCO(A11,D11,ODR)
CQ12,CQ12S=LINCO(A12,D12,ODR)

PlZ=(PIN-PR)/2,0
P2Z=01Z
P57Z=PlZ
P68Z=PlZ
P79Z=PlZ
P81Z=PlZ
P11Z=PlZ
P12Z=PlZ

Q7Z=0.0
Q8Z=0.0
Q9Z=0.0
Q10Z=0.0
Q11Z=0.0
Q12Z=0.0
Q57Z=0.0
Q68Z=0.0
Q79Z=0.0
Q81Z=0.0

All=PI*(D11*D11-D11R*D11R)/4.0
Al2=PI*(D12*D12-D12R*D12R)/4.0

D11=DLR
D12=DLR
D11R=DRR
D12R=DRR

A5S=A5*A5
A6S=A6*A6
A7S=A7*A7
A8S=A8*A8

L57=LA5
A68=LA6
L79=LA7
L81=LA8

LEP57=LEP5
LEP79=LEP7+LDV7+LBV7
LEP68=LEP6
LEP81=LEP8+LDV8+LBV8

V57=VP5
V68=VP6
V79=VP7+V7B1+V7B2+V7B3+VDV7+VBV7
V81=VP8+V8B1+V8B2+V8B3+VDV8+VBV8

LDV7=SPECV(PDR7,QDR7,DDV7)
LDV8=LDV7
LBV7=SPECV(PBR7,RER7,DBV7)
LBV8=LBV7
VBV8=VBV7
VDV8=VDV7

DRE=ODRE-2.0*THRE
BIR=BOI+2.0*((1.+POIS)*ODRE*ODRE+(1.-POIS)*DRE*DRE)/...
(E*(ODRE*ODRE-ORE*ORE))

CEL=CELCC/(PCEL*983.4)
CIL=CILCC/(PCIL*983.4)

XRZ=0.0
ZRDZ=0.0

D1=3.*DLV
D2=D1

LC=0.5*(LCY-TR)

DYNAMIC

**** PROCEDURE SERVO-VALVE *****

```

PROCED Q1,Q2,Q3,Q4=SERVO(AG,KCO,LAMB,PIN,PR,P1,P2,...
                        XV,XVM,RHO1,RHO2,RHOR)
      CEX=KCO*EXP(-LAMB*(XV/XVM)**2)
      IF(XV)10,20,30
10    Q1=CEX*(PIN-P1)
      Q2=AG*SQRT(XV*XV*(PIN-P2)/RHO2)
      Q3=AG*SQRT(ZV*ZV*(P1=PR)/RHOR)
      Q4=CEX*(P2-PR)
      GO TC 40
20    Q1=CEX*(PIN-P1)
      Q2=CEX*(PIN-P2)
      Q3=CEX*(P1-PR)
      Q4=CEX*(P2-PR)
      GO TO 40
30    Q1=AG*XV*SQRT((PIN-P1)/RHO1)
      Q2=CEX*(PIN-P2)
      Q3=CEX*(P1-PR)
      Q4=AG(XV(SQRT((P2-PR)/RHOR)
40    CONTINUE
ENDPRO

```

**** PROCEDURE KPRO *****

```

PROCEED K5,K6,K7,K8,K9,K10=KPRO(P1,P2,P5,P6,P7,P8,P9,P10,K5P,...
                                K5M,K6P,K6M,K7P,K7M,K8P,K8M,K9P,K9M,K10P,K10M)
      IF(P1.GE.P5)GO TO 100
      K5=K5M
      GO TO 101
100    K5=K5P
101    IF(P2.GE.P6)GO TO 102
      K6=K6M
      GO TO 103
102    K6=K6P
103    IF (P5.GE.P7)GO TO 104
      K7=K7M
      GO TO 105
104    K7=K7P
105    IF(P6.GE.P8)GO TO 106
      K=K8M
      GO TO 107
106    K8=K8P
107    IF(P7.GE.P9)GO TO 108
      K9=K9M
      GO TO 109
108    K9=K9P
109    IF(P8.GE.P10)GO TO 110
      K10=K10M
      GO TO 111
110    K10=K10P
111    CONTINUE
ENDPRO

```


*** PROCEDURE EFFECTIVE LINE LENGTH ***

```

PROCED LE57=PRO57(LEP57,L57,Q57,D5,RHO57,MU57)
  CLE57=Q57*RHO57/(MU57*D5)
  IF(CLE57.LT.785.4)GO TO 200
  LE57=L57+LEP57
  GO TO 201
200  LE57=L57+1.273E-03*CLE57*LEP57
201  CONTINUE
ENDPRO

```

```

PROCED LE68=PRO68(LEP68,L68,Q68,D6,RHO68,MU68)
  CLE68=Q68RHO68/(MU68*D6)
  IF(CLE68.LT.785.4)GO TO 202
  LE68=L68+LEP68
  GO TO 203
202  LE68=L68+1.273E-03*CLE68*LEP68
203  CONTINUE
ENDPRO

```

```

PROCED LE79=PRO79(LEP79,L79,Q79,D7,RHO79,MU79)
  CLE79=Q79*RHO79/(MU79*D7)
  IF(CLE79.LT.785.4)GO TO 204
  LE79=L79+LEP79
  GO TO 205
204  LE79=L79+1.273E-03*CLE79*LEP79
205  CONTINUE
ENDPRO

```

```

PROCED LE81=PRO81(LEP81,L81,Q81,D8,RHO81,MU81)
  CLE81=Q81*RHO81/(MU81*D8)
  IF(CLE81.LT785.4)GO TO 206
  LE81=L81+LEP81
  GO TO 207
206  LE81=L81+1.273E-03*CLE81*LEP81
207  CONTINUE
ENDPRO

```

*** PROCEDURE MASS OF OIL ***

```

PROCED MDOIL,MT=MOPRO(MR,XRD,RHO11,RHO12,V11,V12,V11D,
  V12D,RHO57,RHO68,RHO79,RHO81,RHO1,RHO2,V1,V2,V57,V68,
  V79,V81,...
  RHOR,VR)
  IF(XRD.GE.0.)GO TO 400
MOIL=RHO11*V11+RHO79*V79+RHO57*V57+RHO*V1+RHOR*VR
  GO TO 401
400  MOIL=RHO12*V12+RHO81*V81+RHO68*RHO2*V2+RHOR*VR
  MDOIL=RHO12*V12D
401  MT=MR+MOIL
ENDPRO

```


$P1D = (Q1 - Q3 - Q5) / (V1 * B1I)$
 $P2D = (Q2 - Q4 - Q5) / (V2 * B2I)$
 $P57D = (Q5 - Q7) / (B57I * V57)$
 $P68D = (Q6 - Q8) / (B68I * V68)$
 $P79D = (Q7 - Q9) / (B79I * V79)$
 $P81D = (Q8 - Q10) / (B81I * V81)$
 $P11D = (Q11 - Q1L - V11D) / (V11I * V11)$
 $P12D = (Q12 + Q1L + V12D) / (B12I * V12)$

$P5 = 2.0 * P57 - P7$
 $P7 = 2.0 * P79 - P9$
 $P9 = (Q9 - Q11) / CEL$
 $P6 = 2.0 * P68 - P8$
 $P8 = 2.0 * P81 - P10$
 $P10 = (Q10 - Q12) / CEL$

*** LINE AND RAM FLOWS ***

$Q5 = A5 * \text{SQRT}(2.0 * (P1 - P5) / (RHO5 * K5))$
 $Q6 = A6 * \text{SQRT}(2.0 * (P2 - P6) / (RHO6 * K6))$

THE FOLLOWING EQUATIONS IN IMPLICIT FORM WERE INSERTED IN AN EFFORT TO CLEAR THE ALGEBRAIC LOOP PROBLEM. IT DID NOT WORK.

THE NEXT LOGICAL STEP WOULD BE TO COMPACT ALL EQUATIONS SUCH THAT EACH VARIABLE IS EQUATED ONLY TO ITSELF OR A VARIABLE WHICH IS DIRECTLY COUPLED TO AN INTEGRAL.

$Q7 = \text{IMPL}(Q7Z, 0.001, Q7CC)$
 $Q7C = ((P5 - P7 - CQ57S * RHO57 * \text{ABS}(Q57(-0.5 * RHO7 * K7 * Q7Q7 / Q5S) \dots$
 $\quad / (CQ57 * MU57 * LE57)) * 2. - Q5$

$Q7CC = Q7C$
 $Q8 = \text{IMPL}(Q8Z, 0.001, Q8CC)$
 $Q8C = ((P6 - P8 - CQ68S * RHO68 * Q68 * \text{ABS}(Q68) - 0.5 * RHO8 * K8 * Q8 / A6S) \dots$
 $\quad / (CQ68 * MU68 * LE68)) * 2. - Q6$
 $Q8CC = Q8C$

$Q9 = \text{IMPL}(Q9Z, 0.001, Q9CC)$
 $Q9C = ((P7 - P9 - CQ79S * RHO79 * Q79 * \text{ABS}(Q79) - 0.5 * RHO9 * K9 * Q9 * Q9 / A7S \dots$
 $\quad / (CQ79 * MU79 * LE79)) * 2. - Q7$
 $Q9CC = Q9C$

$Q10 = \text{IMPL}(Q10Z, 0.001, Q10CC)$
 $Q10C = ((P8 - P10 - CQ81S * RHO81 * Q81 * \text{ABS}(Q81) - 0.5 * RHO10 * K10 * Q10 * Q10 \dots$
 $\quad / A8S) / (CQ81 * MU81 * LE81)) * 2. - Q8$
 $Q10CC = Q10C$

$Q11 = \text{IMPL}(Q11Z, 0.001, Q11C)$
 $Q11C = (P9 - P11 - CQ11S * RHO11 * Q11 * \text{ABS}(Q11)) / (CQ11 * MU11 * L11)$
 $Q12 = \text{IMPL}(Q12Z, 0.001, Q12C)$
 $Q12C = (P10 - P12 - CQ12S * RHO12 * Q12 * \text{ABS}(Q12)) / (CQ12 * MU12 * L12)$

Q57=IMPL(Q57Z,0.0001,Q57CC)
Q57C=(P5-P7-CQ57S*RHO57*Q57*ABS(Q57)-0.5*RHO7*K7*Q7*Q7/A5S)...
/(CQ57*MU57*LE57)
Q57CC=Q57C

Q68=IMPL(Q68Z,0.001,Q68CC)
Q68C=(P6-P8-CQ68S*RHO68*ABS(Q68)-0.5*RHO8*K8*Q8*Q8/A6S)...
/(CQ68*MU68*LE68)
Q68CC=Q68C

Q79=IMPL(Q79Z,0.001,Q79CC)
Q79C=(P7-P9-CQ79S*RHO79*Q79*ABS(Q79)-0.5*RHO9*K9*Q9*Q9/A7S)...
/(CQ79*MU79*LE79)
Q79CC=Q79C

Q81=IMPL(Q81Z,0.001,Q81CC)
Q81C=(P8-P10-CQ81S*RHO81*ABS(Q81)-0.5*RHO10*K10*Q10*Q10...
/A8S)/(CQ81*MU81*LE81)
Q81CC=Q81C

QIL=CIL*(P11-P12)

B1I=CFA/P1+BI1
B2I=CFA/P2+BI2
BRI=CFA/PR+BIR
B5I=CFA/P5+BI5
B6I=CFA/P6+BI6
B7I=CFA/P7+BI7
B8I=CFA/P8+BI8
B9I=CFA/P9+BI9
B10I=CFA/P10+BI10
B11I=CFA/P11+BI11
B12I=CFA/P12+BI12
B57I=CFA/P57+BI57
B68I=CFA/P68+BI68
B79I=CFA/P79+BI79
B81I=CFA/P81+BI81

****DENSITY VALUES ****

RHOR=8.256E-05+8.423E-05*PR*BRI
ROH1=8.256E-05+8.423E-05*P1*B1I
RHO2=8.256E-05+8.423E-05*P2*B2I
RHO5=8.256E-05+8.423E-05*P5*B5I
RHO6=8.256E-05+8.423E-05*P6*B6I
RHO7=8.256E-05+8.423E-05*P7*B7I
RHO8=8.256E-05+8.423E-05*P8*B8I
RHO9=8.256E-05+8.423E-05*P9*B9I
RHO10=8.256E-05+8.423E-05*P10*B10I
RHO11=8.256E-05+8.423E-05*P11*B11I
RHO12=8.256E-05+8.423E-05*P12*B12I
RHO57=8.256E-05+8.423E-05*P57*B57I
RHO68=8.256E-05+8.423E-05*P68*B68I
RHO79=8.256E-05+8.423E-05*P79*B79I
RHO81=8.256E-05+8.423E-05*P81*B81I

*** VISCOSITY EQUATIONS ***

MU57=8.198E-06*EXP(P57*B57I)
MU68=8.198E-06*EXP(P68*B68I)
MU79=8.198E-06*EXP(P79*B79I)
MU81=8.198E-06*EXP(P81*B81I)
MU11=8.198E-06*EXP(P11*B11I)
MU12=8.198E-06*EXP(P12*B12I)

LIST OF REFERENCES


1. Naval Sea Systems Command, Naval Ship's Technical Manual, NAVSEA 0901-LP-561-001, "Submarine Steering and Diving Systems" (Chapter 561, Change 1), Pg. 2, 1 November 1977.
2. Merritt, H.E., Hydraulic Control Systems, p. 140, Wiley, 1967.
3. Atkinson, T., CODE 260.43, Mare Island Naval Shipyard, Vallejo, CA., Personal Communication.
4. Wilcox, W., Hydraulic Divison, Naval Sea Systems Command, Washington, D.C., Personal Communications.
5. Serchuk, A., "Fluid Power: Continuing to Nibble at Other Systems," Factory Report, v. 8No.9, p.34-38, September 1975.
6. Leslie, R.L., and Sculthrope, H.J., "Hydraulic Fluids Compatible with Metal working Fluids", p. 165-167. Lubrication Engineering, v. 28, No.5, May 1972.
7. Salamandra, T.S., "Life of Rubber O-Rings Subjected to Reciprocating Motion," Machines and Tooling, v. 44No.8, p. 37-39, 1973.
8. Naval Sea Systems Command, Naval Ship's Technical Manual, NAVSEA S9086-S4-STM-000, "Hydraulic Equipment (Power Transmission and Control)" Chapter 556, Revision 1), paragraph 556-5.4, 1 April 1979.
9. Wilcox, W., op cit.
10. Engineering Division, Crane Company, Technical Paper No. 410, Flow of Fluids Through Valves, Fittings, and Pipe, 13th Ed., p. 1-3, 1973.
11. Merritt, H.E., op. cit.
12. Naval Sea Systems Command, Naval Ship's Technical Manual, NAVSEA 0901-LP-450-0002, "Lubricating Oils, Grease, and Hydraulic Fluids, and Lubrication Systems," (Chapter 9450, Change 4) paragraph 9450.7, 1 June 1977.
13. Ibid., Fig. 9450-1.
14. Blackburn, J.F., and others, Fluid Power Control, p.20, The Massachusetts Institute of Technology Press, 1960.
15. Crane Company, op. cit., p. B-3.
16. Merritt, H.E., op. cit., p. 11.

17. Blackburn, J.F., op. cit., p. 21.
18. Merritt, H.E., op. cit., p. 8.
19. Naval Sea Systems Command, Naval Ship's Technical Manual, NAVSEA 0901-LP-561-0001, "Submarine Steering and Diving Systems," (Chapter 561, Change 1), paragraph 561.2.9 and Tab. 561-2.
20. Naval Sea Systems Command, Low Noise Electrohydraulic Flow Control Servovalve, "Model SV-438-10P," NAVSEA 0948-LP-064-4012, Change 2, 17 October 1977.
21. Merritt, op. cit., p. 53.
22. Ibid., p. 81.
23. Ibid., p. 89.
24. Ibid., p. 32-46.
25. Naval Sea Systems Command, Naval Ship's Technical Manual, NAVSEA 0901-LP-561-0001, "Submarine Steering and Diving Systems," (Chapter 561, Change 1), p. 27 and Tab. 561-4.
26. Mare Island Naval Shipyard, Blueprint, Submarine SSN 594 Hydraulic System Valve Data Sheet, Bureau of Ships No. SSN594-516-1969644-K, 20 November 1978.
27. Crane Company, op. cit.

INITIAL DISTRIBUTION LIST

	No. of copies
1. Defense Technical Information Center Cameron Station Alexandria, Virginia 22314	2
2. Library, Code 0142 Naval Postgraduate School Monterey, California 93940	2
3. Department Chairman, Code 69 Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93940	2
4. Dr. Thomas, M. Houlihan, Code 69Hm Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93940	5
5. Dr. R. H.Nunn, Code 69Nn Department of Mechanical Engineering Naval Postgraduate School Monterey, California 93940	1
6. LT Michael J. Bower Mare Island Naval Shipyard Code 330.6 Vallejo, California 94592	1





Thesis

B7475

c.1

Bower

189128

Submarine hydraulic
control analysis.

Thesis

B7475

c.1


Bower

189128

Submarine hydraulic
control analysis.

thesB7475

Submarine hydraulic control analysis.



3 2768 002 07369 4

DUDLEY KNOX LIBRARY